

Desktop Barcode Printer Compact Printer Series

CP-2140 203dpi



CP-2140E 203dpi
(Internal Ethernet)



CP-3140 300dpi



NEW!

CP-3140E 300dpi
(Internal Ethernet)



Features

- Compact size and 300M ribbon capacity
- Easy media and ribbon loading
- Multiple communication interfaces
- A variety of paper sensor system for diverse applications
- Ribbon wound ink-side out or ink-side in available
- Printing speed up to 4 ips, and expanded memory for font, graphic and form storage
- Module design and easy maintenance
- Four Auto-Calibration Modes
- Printing noise improved
- Supports 1D/GS1 Data bar, 2D/Composite codes and QR barcodes, and windows true type font download available

CP series printers offer the cutter as optional accessory



*Compact size printer with large 300M long ribbon capacity
Easy media and ribbon loading*



Applications

Clothing tag
Retail tag
Shelf labeling
Patient tracking
Inventory labeling
Postal & mailing
Shipping & receiving
Document labeling
Stationeries labeling
Parts marking

ARGOX
Empower the Barcode



Product Values



CP-2140

CP-3140



> CP-2140/CP-3140 interface



CP-2140E

CP-3140E



> CP-2140E/CP-3140E interface

CP-2140 / CP-2140E

The compact CP-2140 desktop printer not only saves space, it lets you install a large 300M long ribbon for bigger printing demands. Ribbons and media are easy to load, and you can select for ribbon ink-side in or ink-side out. A media sensor system delivers greater flexibility for diverse media and applications. A head-open switch initiates auto-calibration for more precise printing. Multiple communication interfaces include parallel (CP-2140), RS-232, USB, and optional Ethernet (CP-2140E).

The CP-2140 prints at 203dpi resolution and a speed of 4ips. Standard memory includes 4MB Flash and 8MB SDRAM. The printer has a modular design for easy maintenance, and printing noise is minimal. It supports the Windows 7 OS, 1D/GS1 Data bar, 2D/Composite codes, QR barcodes, and Windows TrueType fonts. You can use the CP-2140 as a standalone printer by adding the Argokee keyboard, and a scanner.

With the CP-2140 you get the convenience of a small size printer with the functions of a large printer and at a more competitive cost. It's the perfect printer for applications such as clothing tags, self-labeling, mailing, retail, shipping & receiving, inventory and patient tracking. The new CP-2140 and CP-2140E printers continues Argox's leading position in innovation, price, and performance.

CP-3140 / CP-3140E

The CP-3140 compact desktop printer offers 300dpi resolution and larger memory for high quality printing. The high print resolution is perfect for producing text and graphics for applications such as clothing labels, photos on hospital I.D. bracelets, and labels for small retail items such as jewelry.

The CP-3140 holds a 300M long ribbon for large printing demands and for less frequent ribbon changes. Loading media and ribbons is quick and easy. A paper sensor system supports diverse media and you can select ribbon ink-side in or ink-side out. Four auto-calibration modes deliver more precise printing. The printer provides multiple communication interfaces including parallel (CP-3140), RS-232, and USB, and optional Ethernet (CP-3140E).

The CP-3140 prints at a speed of 4ips and onto media of up to 50-inches in length. Standard memory includes 8MB Flash and 8MB SDRAM. The printer's modular design simplifies maintenance. It supports 1D/GS1 Data bar, 2D/Composite codes, QR barcodes, and Windows TrueType font download. The CP-3140 provides high quality printing for applications that require enhanced printing of text and graphics. The new CP-3140 and CP-3140E printers are space-saving, flexible, and delivers outstanding print performance.








> Standalone mode with Argokee

> Media Shaft Design for stabilizing paper

> Movable Reflective Sensor

> Center Fixed Transmissive Sensor

> External media stacker for 8.5" OD paper roll

| Specifications | CP-2140 | CP-2140E | CP-3140 | CP-3140E |
|--------------------------|---|----------|--|----------|
| Printing Method | Direct Thermal / Thermal Transfer | | | |
| Printing Resolution | 203 dpi(8 dots/mm) | | 300 dpi(12 dots/mm) | |
| Printing Speed | 2~4ips (50.8~101.6mm/s) | | 1~up to 4ips (25.4~101.6mm/s) | |
| Printing Length | Max 100"(2540mm) / Min 0.2" (5mm) | | Max 50"(1270mm) / Min 0.2"(5mm) | |
| Printing Width | Max 4.1"(104mm) | | | |
| Memory | 8MB DRAM(5MB user available) 4MB Flash ROM(2MB user available) | | 8MB DRAM(5MB user available) 8MB Flash ROM(6MB user available) | |
| CPU | 32 bit RISC microprocessor | | | |
| Sensors | Media gap & black line Reflective sensor x 1 (movable)& Transmissive sensor x 1 (Center fixed) / Head open switch / Ribbon end sensor | | | |
| Operation Interface | LED indicator (Power/Ready)x 2, Button(Feed) x 1 | | | |
| Communication Interface | CP-2140, CP-3140: Parallel, USB, RS-232(Baud rate: 2400~115200 bps) CP-2140E, CP-3140E: Ethernet, USB, RS-232(Baud rate: 2400~115200 bps) | | | |
| Fonts | Internal character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23" H (1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x24 4 direction 0° ~ 270° rotation Soft fonts are downloadable | | | |
| 1D Barcodes | <p>PPLA:Code 39, UPC-A, UPC-E, Code 128 subset A/B/C, EAN-13, EAN-8, HBIC, Codabar, Plessey, UPC2, UPC5, Code 93, Postnet, UCC/EAN-128, UCC/EAN-128 K-MART, UCC/EAN-128 Random Weight, Telepen, FIM, Interleave 2 of 5 (Standard/with modulo 10 checksum/with human readable check digit/with modulo 10 checksum & shipping bearer bars), GS1 Data bar (RSS)</p> <p>PPLB:Code 39 Std. & Extended, UPC-A, UPC-E, UPC-Interleaved 2 of 5, Code 39 with check sum digit, Code 93, EAN-13, EAN-8 (Standard, 2/5digit add-on), Codabar, Postnet, Code128 subset A/B/C, Code 128 UCC (shipping container code), Code 128 auto, UCC/EAN code 128 (GS1-128) Interleave 2 of 5, Interleaved 2 of 5 with check sum, Interleaved 2 of 5 with human readable check digit, German Postcode, Matrix 2 of 5, UPC Interleaved 2 of 5 EAN-13 2/5 digit add-on, UPCA 2/5 digit add-on, UPCE 2/5 digit add-on, GS1 Data bar (RSS)</p> <p>PPLZ(CP-2140Z Only):Code39, UPC-A, UPC-E, Postnet, Code128 subset A/B/C, Interleave 2 of 5, Interleaved 2 of 5 with check sum Interleaved 2 of 5 with human readable check digit, Code 93, Code 39 with check sum digit, MSI, EAN-8, Codabar, Code 11, EAN-13, Plessey, GS1 Data bar (RSS) Industrial 2 of 5, Standard 2 of 5, Logmars</p> | | | |
| 2D Barcodes | <p>PPLAZ:MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, Composite Codes, Aztec Barcode(PPLA only)</p> <p>PPLB:MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, Composite Codes, Aztec Barcode</p> | | | |
| Graphics | <p>PPLA: PCX, BMP, IMG, GDI and HEX format files PPLB: PCX, Binary raster, BMP and GDI PPLZ: GRF, Hex and GDI</p> | | | |
| Emulation | <p>CP-2140, CP-2140E, CP-3140, CP-3140E: PPLA, PPLB CP-2140Z: PPLZ</p> | | | |
| Software - Label editing | Windows Driver (Windows XP/Vista/ 7/ 8) ,BarTender® from Seagull Scientific | | | |
| Software - Utility | Printer Utility \ Font Utility | | | |
| Media Type | Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper and fabric label | | | |
| Media | <p>Max Width: 4.3"(110mm) Min Width: 1"(25.4mm) Thickness: 0.0025"~0.01"(0.0635~0.254mm) Max roll capacity(OD): 5"(127mm) / Core size: 1"(25.4mm) Max roll capacity(OD): 4.5"(114.3mm) / Core size: 0.5"(12.7mm) (optional) Max roll capacity(OD): 4.7"(120mm) / Core size: 1.5"(38.1mm) (optional)</p> | | | |
| Ribbon | <p>Ribbon roll – max OD: 2.6"(67mm) Ribbon Length: max 300m Core size – ID: 1"(25.4mm) Ribbon Width: 1"~4" Wax, Wax/Resin, Resin (Ribbon wound ink-side out or ink-side in available)</p> | | | |
| Dimensions | L 273mm x W 225mm x H 186mm | | | |
| Weight | 2.1kg | | | |
| Power Source | Universal Switching Power Supply AC Input: 100~240V, 1.8A, 50~60Hz DC Output: 24V 2.4A | | Universal Switching Power Supply AC Input: 100~240V,1.5A, 50-60Hz, DC Output: 24V, 2.91A | |
| Operation Environment | Operation Temperature: 40°F~100°F (4°C~38°C), 10% ~ 90% non-condensing, Storage Temperature: -4°F~122°F (-20°C~50°C) | | | |
| Optional Items | Guillotine Cutter, Rotary Cutter, Stacker, RTC Card, ArgoKee | | | |
| Media Stacker | Optional | | Standard | |
| Agency Listing |      | | | |

